

## **HTI Reflector**



## Areas of application

- Concert Lighting
- Club & Disco
- Stage & Theatre
- Studio, TV, & Film
- Architecture & Architainment

### Product features and benefits

- Robust design with precision reflector alignment
- Consistent lumen output over the life of the lamp
- Higher luminous efficacy than conventional HID lamps provides higher fixture efficiency

# Product family datasheet

## Technical data

	General Product Information				
Product description	Product number (Americas)	Product name (Americas)	Family brand	Global order reference	
HTI 250 W/32C	54089	HTI 250 W/32C 2/CS 1/SKU	HTI	HTI 250W/32 C W	
HTI 250W/32	54081	HTI 250 W/32 2/CS 1/SKU	HTI	HTI 250W/32	
HTI 400 W/24	54083	HTI 400 W/24 2/CS 1/SKU	HTI	HTI 400W/24 W.	
	Electrical Data			Physical Attributes & Dimensions	
Product description	Nominal wattage	Nominal voltage	Nominal current	Lamp base	
HTI 250 W/32C	250 W	45.0 V	6 A	FaXP2.5-2x65	
HTI 250W/32	250 W	45.0 V	6 A	FaXP2.5-2x65	
HTI 400 W/24	400 W	55.0 V	7.3 A	FaXP2.5-2x65	
Product description	Diameter	Diameter (in)	Diameter	Length	

Product description	Diameter	Diameter (in)	Diameter	Length
HTI 250 W/32C	67.0 mm	2.638 in	67.0 mm	73.0 mm
HTI 250W/32	67.0 mm	2.638 in	67.0 mm	73.0 mm
HTI 400 W/24	67.0 mm	2.638 in	67.0 mm	73.0 mm
	-			

			Lifetime Data	Environmental & Regulatory Information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)
Product description	Connector: presence	Product weight	Nominal lifetime	Primary article identifier
HTI 250 W/32C	Yes	115.00 g	250 hr	4050300021805
HTI 250W/32		106.00 g	250 hr	4050300226576
HTI 400 W/24	Yes	115.00 g	250 hr	4050300228327

Product description	Declaration no. in SCIP database	Candidate list substance 1
HTI 250 W/32C	No declarable substances contained	No declarable substances contained
HTI 250W/32	No declarable substances contained	No declarable substances contained
HTI 400 W/24	No declarable substances contained	No declarable substances contained

## Product family datasheet

#### Safety advice

Because of their high luminance, UV radiation and high internal pressure during operation, HTI lamps may only be operated in enclosed lamp casings specially constructed for the purpose. Appropriate filters must ensure that UV radiation is reduced to an acceptable level. Mercury is released if the lamp breaks. Special safety precautions must be taken. Information on safety and handling is available on request or can be found in the leaflet included with the lamp or in the operating instructions.

#### Application advice

For more detailed application information and graphics please see product datasheet.

#### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.