## Product family datasheet

# LEDriving HLM EASY T19



Cool White color temperature of 6,000 K

Better visibility thanks to daylight effect



Allowing a high compatibility and an

easy installation.



OSRAM

LED replacement for conventional T19 high and low beam lamps Reduced glaring thanks to an optimal light distribution

## LED high and low beams lamps with plug & play system for motorcycles.

The OSRAM LEDriving HLM EASY represent an easy solution to upgrade conventional motorcycle headlights with cool white LED light – with a color temperature of 6,000 K, they provide a stylish and modern look as well as superior brightness. Equipped with the latest LED technology and a very compact design, these lamps allow high compatibility and an easy installation for a wide range of motorcycle models. The LEDriving HLM EASY lamps are 12V and AC/DC compatible and offer a long service life. These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

Product family datasheet | LEDriving HLM EASY T19 © 2025, OSRAM GmbH. All rights reserved.





## Product family datasheet

### Technical data

	Product information		General P Informatio		Electrical I	Data	
Product description	Application (Category and Product specific)	Product type (off- road vs. on-road)	Global ord reference	ler	Power input	Nominal voltage	
LEDriving HLM EASY T19	Mainly used for headlight applications	Off-road T19	7335DWE	SY	6.0 W / 5.5 W	13.5 V	
		Photometric Data			Physical Attributes & Dimensions		
Product description	Nominal wattage	Nominal lu flux	uminous	Luminous flux tolerance	Diameter	r Diamete r	
LEDriving HLM EASY T19	5 W	600/500 lr	n	±15 %	18.4 mm	18.4 mm	
	Lifetime Data C		Capabilities	Informatio	Environmental & Regulatory Information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)		
Product description	Lifespan B3	Lifespan Tc	Technology	Primary ar identifier	ticle	Candidate list substance 1	
LEDriving HLM EASY T19	500 hr	1000 hr	LED	40621723 40621723	•	Lead	

Product description	CAS No. of substance 1	Safe use instruction	Declaration no. in SCIP database
LEDriving HLM EASY T19	7439-92-1	The identification of the Candidate List substance is sufficient to allow safe use of the article.	efa593e8-2c11-4e97- 9734-d514687a1b08   5ec6e727-7f8a- 4bc0-ac15- c8ce50c92a5f

## Product family datasheet

#### Download Data

 File

 User instruction

 GPRS\_Safety symbols instructions

#### Legal advice

These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

#### **Application advice**

For more detailed application information and graphics please see product datasheet.

#### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.